

Moisture analyser KERN MLB-C



Features

- Back-lit LCD graphic display, digit height 14 mm
 - 1 Moisture display in %
 - 2 Current moisture content in %
 - 3 Printout in moisture %
 - 4 Type of drying *Standard*
 - 5 Switch off mode
 - 6 Previous drying time
 - 7 Current temperature
 - 8 Drying process active
- **Halogen quartz glass heater** 400 W
- **Memory for automatic** sequence of 20 complete drying programs (12 free digits for each memory)
- The last value measured remains on the display until it is replaced by a new measurement
- The large ventilation slots in the heating cover combined with the sample viewing window in the form of a metal grid, ensure that moisture escapes quickly and this leads to shorter drying times
- Drying programs with optimised drying characteristics for rapid sample warming and therefore shorter drying times
- **10 sample plates included**
- **Application handbook:** There are many practical examples in the operating instructions

STANDARD

CAL EXT

MEMORY

RS 232

GLP

PROTOCOL

UNIT

230 V

FORCE

1 DAY

3 YEARS

WARRANTY

OPTION

DKD

+3 DAYS

KERN	MLB 50-3C
Readout [d]	0,001 g / 0,01 %
Weighing range [Max]	50 g
Reproducibility, weight of sample 2 g	0,24 %
Reproducibility, weight of sample 10 g	0,04 %
Display after drying (Display can be switched over at any time)	
Moisture [%] = Moisture content (M) from wet weight (W)	0 - 100 %
Dry content [%] = Dry weight (D) from (W)	100 - 0 %
ATRO [%] [(W-D) : D] · 100%	0 - 999 %
Temperature range	40 - 160 °C in steps up to 1°C
Drying modes	<ul style="list-style-type: none">• Standard drying• Drying in levels• Gentle drying• Rapid drying
Switch off criteria	<ul style="list-style-type: none">• When the set time has expired (1 min - 10 h)• When a constant weight per adjustable time unit has been reached (1 - 59 sec)
Recall of measurement	Interval can be set from 1 - 180 sec (Only when used with printer KERN YKB-01 or PC)
Overall dimensions WxDxH	206x333x195 mm
Net weight	4,9 kg
Option DKD Calibr. Certificate	963-127

Accessories

- **Sample plates aluminium**, Ø 92 mm. Unit of 80 pieces, KERN MLB-A01
- Round fiberglass filter, e.g. for samples that splash or become encrusted, unit of 80 pieces, KERN RH-A02
- **9 Temperature calibration set** consisting of measuring sensor and display device. Highly accurate temperature adjustment through optimised position of the measuring sensor, KERN MLB-A12
- **Protective working cover** standard, can be reordered, KERN ALS-A02
- **Suitable printers** see page 138

KERN Pictograms



Internal adjusting (CAL): Quick setting of the balance's accuracy with internal adjusting weight (motordriven).



Adjusting program (CAL): For quick setting of the balance's accuracy. External adjusting weight required.



Memory: Balance contains memories, e.g. for item data, weighing data, tare weights etc. PLU.



Data interface RS-232: To connect the balance to a printer, PC or network.



RS 485 data interface: To connect the balance to a printer, PC or other peripheral devices. High tolerance against electromagnetic disturbance.



USB data interface: To connect the balance to a printer, PC or other peripheral devices.



Bluetooth data interface: To transfer data from the balance to a printer, PC or other peripheral devices.



Control outputs (optocoupler, digital I/O): to connect relays, signal lamps, valves, etc.



Interface for second balance: for direct connection of a second balance.



Network interface: For connecting the scale to an Ethernet network. With KERN products you can also use a universal RS-232/LAN converter.



GLP/ISO record keeping: of weighing data with date, time and identification-no. Only with printers from KERN.



Piece counting: Reference quantities selectable. Display can be switched from piece to weight.



Recipe level A: Separate memory for the weight of the tare container and the recipe ingredients (net total).



Recipe level B: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through displays.



Recipe level C: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through displays. Additional convenient functions, such as bar-code and back calculation functions.



Percentage determination: Determining the deviation in % from the target value (100%).



Weighing units: Can be switched to e. g. non-metric units at the touch of a key. See balance model. Please refer to KERN's website for more details.



Weighing with tolerance range: Upper and lower limiting can be programmed individually, e.g. dosing/sorting and portioning.



Vibration-free weighing: (Animal weighing program) Vibrations are filtered out so that a stable weight is obtained.



Spray and dust protection IPxx: The type of protection is shown by the pictogram. For details see the glossary.



Stainless steel: the balance is protected against corrosion.



Suspended weighing: load support with hook on the underside of the balance.



Battery operation: Ready for battery operation. The battery type is specified for each device.



Rechargeable battery pack: rechargeable set.



Mains adapter: 230V/50Hz in standard version for Germany. On request GB, AUS or USA version.



Power supply: integrated in balance. 230V/50Hz in Germany. More standards e. g. GB, AUS, USA on request.



Strain gauges: Electrical resistor on an elastic deforming body.



Tuning fork principle: A resonating body is electromagnetically excited, causing it to oscillate.



Electromagnetic force compensation: Coil in a permanent magnet. For the most accurate weighings.



Single cell technology: Advanced version of the force compensation principle with the highest level of precision.



Verification possible: The time required for verification is specified in the pictogram.



DKD calibration possible: The time required for DKD calibration is shown in days in the pictogram.



Package shipment: The time required to manufacture the product internally is shown in days in the pictogram.



Pallet shipment: The time required to manufacture the product internally is shown in days in the pictogram.



Warranty: The warranty period is shown in the pictogram.

Precision is our business

To ensure the high precision of your balance KERN offers you the appropriate test weight package for your balance, consisting of the test weight, box and DKD certificate, as proof of its accuracy ... the best pre-requisite for proper balance calibration.

In the extensive KERN test weight range, you will find test weights in the international OIML error limit classes: E1, E2, F1, F2, M1, M2, M3 with weights from 1 mg - 2000 kg.

The KERN DKD calibration laboratory for electronic balances and weights has been accredited by DKD since 1994 and today is one of the most modern and best-equipped DKD calibration laboratories for balances, test weights and force-measurement in Europe.

(DKD = German Calibration Service)

Thanks to the high level of automation, we can carry out DKD calibration of balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

Range of services:

- DKD calibration of balances with a maximum load of up to 6 t
- DKD calibration of weights in the range of 1 mg – 500 kg
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DKD calibration certificates in the following languages
D, GB, F, I, E, NL, PL

Do you have questions about your scale, the corresponding test weight or the calibration service? Your KERN specialist dealer will be pleased to assist you.

Your KERN specialist dealer: