

IP protected bench scale KERN FFN-N



Robust, space-saving bench scale, protected by stainless steel and IP65, also with EC type approval [M]

Features

- **1 Ideal for the food industry**
- **2 Ideal for the robust industry**
- **High mobility:** thanks to battery operation, compact construction and low weight, it is suitable for use in several locations (production, kitchen, sales office)
- **Stainless steel housing,** rust-proof and easy to clean
- **Level indicator and foot screws** to level the balance precisely, fitted as standard, to give the most accurate weighing results
- **Carrying grips on the underside** of the scale for easy transportation

- **3 IP65:** Protected against dust and water splashes (only when using rechargeable battery pack)
- Supports you in your HACCP-compliant quality system

Technical data

- Large backlit LCD display, digit height 25 mm
- Dimensions of weighing plate (stainless steel) WxD 230x190 mm
- Overall dimensions 230x300x130 mm
- Rechargeable battery pack internal, standard, operating time up to 50 h, charging time approx. 12 h
- Net weight approx. 3,2 kg
- Permissible ambient temperature 0 °C / 40 °C

Accessories

- **Tare pan made from stainless steel,** ideal for weighing loose small parts, fruit, vegetables etc., WxDxH 370x240x20 mm, KERN RFS-A02

STANDARD

CAL EXT

UNIT

IP 65

INOX

ACCU

230 V

DMS

1 DAY

2 YEARS WARRANTY

OPTION

DKD

+3 DAYS

FACTORY




































M

+3 DAYS

Model	Weighing range [Max] kg	Readout [d] g	Verific. value [e] g	Minimum load [Min] g		Options			
						Verification		DKD Calibr. Certificate	
						KERN		KERN	
KERN									
FFN 1K-4N	1,5	0,2	-	-		-		963-127	
FFN 3K0.5IPN	3	0,5	-	-		-		963-127	
FFN 6K1IPN	6	1	-	-		-		963-128	
FFN 15K2IPN	15	2	-	-		-		963-128	
FFN 25K5IPN	25	5	-	-		-		963-128	
Note: For applications that require verification, please order verification at the same time, initial verification at a later date is not possible. Verification at the factory, we need to know the full address of the location of use.									
FFN 3K1IPM	3	1	1	20		965-227		963-127	
FFN 6K2IPM	6	2	2	40		965-228		963-128	
FFN 15K5IPM	15	5	5	100		965-228		963-128	
FFN 25K10IPM	25	10	10	200		965-228		963-128	

New model

# KERN Pictograms

 <b>CAL INT</b>	<b>Internal adjusting (CAL):</b> Quick setting of the balance's accuracy with internal adjusting weight (motordriven).	 <b>RECIPE A</b>	<b>Recipe level A:</b> Separate memory for the weight of the tare container and the recipe ingredients (net total).	 <b>ACCU</b>	<b>Rechargeable battery pack:</b> rechargeable set.
 <b>CAL EXT</b>	<b>Adjusting program (CAL):</b> For quick setting of the balance's accuracy. External adjusting weight required.	 <b>RECIPE B</b>	<b>Recipe level B:</b> Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through displays.	 <b>230 V</b>	<b>Mains adapter:</b> 230V/50Hz in standard version for Germany. On request GB, AUS or USA version.
 <b>MEMORY</b>	<b>Memory:</b> Balance contains memories, e.g. for item data, weighing data, tare weights etc. PLU.	 <b>RECIPE C</b>	<b>Recipe level C:</b> Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through displays. Additional convenient functions, such as bar-code and back calculation functions.	 <b>230 V</b>	<b>Power supply:</b> integrated in balance. 230V/50Hz in Germany. More standards e. g. GB, AUS, USA on request.
 <b>RS 232</b>	<b>Data interface RS-232:</b> To connect the balance to a printer, PC or network.			 <b>DMS</b>	<b>Strain gauges:</b> Electrical resistor on an elastic deforming body.
 <b>RS 485</b>	<b>RS 485 data interface:</b> To connect the balance to a printer, PC or other peripheral devices. High tolerance against electromagnetic disturbance.	 <b>PERCENT</b>	<b>Percentage determination:</b> Determining the deviation in % from the target value (100%).	 <b>T-FORK</b>	<b>Tuning fork principle:</b> A resonating body is electromagnetically excited, causing it to oscillate.
 <b>USB</b>	<b>USB data interface:</b> To connect the balance to a printer, PC or other peripheral devices.	 <b>UNIT</b>	<b>Weighing units:</b> Can be switched to e. g. non-metric units at the touch of a key. See balance model. Please refer to KERN's website for more details.	 <b>FORCE</b>	<b>Electromagnetic force compensation:</b> Coil in a permanent magnet. For the most accurate weighings.
 <b>BT</b>	<b>Bluetooth data interface:</b> To transfer data from the balance to a printer, PC or other peripheral devices.	 <b>TOL</b>	<b>Weighing with tolerance range:</b> Upper and lower limiting can be programmed individually, e.g. dosing/sorting and portioning.	 <b>SC TECH</b>	<b>Single cell technology:</b> Advanced version of the force compensation principle with the highest level of precision.
 <b>SWITCH</b>	<b>Control outputs (optocoupler, digital I/O):</b> to connect relays, signal lamps, valves, etc.	 <b>MOVE</b>	<b>Vibration-free weighing:</b> (Animal weighing program) Vibrations are filtered out so that a stable weight is obtained.	 <b>M +3 DAYS</b>	<b>Verification possible:</b> The time required for verification is specified in the pictogram.
 <b>DUAL</b>	<b>Interface for second balance:</b> for direct connection of a second balance.	 <b>IP</b>	<b>Spray and dust protection IPxx:</b> The type of protection is shown by the pictogram. For details see the glossary.	 <b>DKD +3 DAYS</b>	<b>DKD calibration possible:</b> The time required for DKD calibration is shown in days in the pictogram.
 <b>LAN</b>	<b>Network interface:</b> For connecting the scale to an Ethernet network. With KERN products you can also use a universal RS-232/LAN converter.	 <b>INOX</b>	<b>Stainless steel:</b> the balance is protected against corrosion.	 <b>DAYS</b>	<b>Package shipment:</b> The time required to manufacture the product internally is shown in days in the pictogram.
 <b>GLP PROTOCOL</b>	<b>GLP/ISO record keeping:</b> of weighing data with date, time and identification-no. Only with printers from KERN.	 <b>UNDER</b>	<b>Suspended weighing:</b> load support with hook on the underside of the balance.	 <b>DAYS</b>	<b>Pallet shipment:</b> The time required to manufacture the product internally is shown in days in the pictogram.
 <b>PCS</b>	<b>Piece counting:</b> Reference quantities selectable. Display can be switched from piece to weight.	 <b>BATT</b>	<b>Battery operation:</b> Ready for battery operation. The battery type is specified for each device.	 <b>3 YEARS WARRANTY</b>	<b>Warranty:</b> The warranty period is shown in the pictogram.

## Precision is our business

To ensure the high precision of your balance KERN offers you the the appropriate test weight package for your balance, consisting of the test weight, box and DKD certificate, as proof of ist accuracy ... the best pre-requisite for proper balance calibration.

In the extensive KERN test weight range, you will find test weights in the international OIML error limit classes: E1, E2, F1, F2, M1, M2, M3 with weights from 1 mg - 2000 kg.

The KERN DKD calibration laboratory for electronic balances and weights has been accredited by DKD since 1994 and today is one of the most modern and best-equipped DKD calibration laboratories for balances, test weights and force-measurement in Europe.  
(DKD = German Calibration Service)

Thanks to the high level of automation, we can carry out DKD calibration of balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

### Range of services:

- DKD calibration of balances with a maximum load of up to 6 t
- DKD calibration of weights in the range of 1 mg – 500 kg
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DKD calibration certificates in the following languages  
D, GB, F, I, E, NL, PL

Do you have questions about your scale, the corresponding test weight or the calibration service ? Your KERN specialist dealer will be pleased to assist you.

## Your KERN specialist dealer: